

INTERFACE:	
1	VCC(5.0V)
2	VSS
3	V0
4	RES
5	E1
6	E2
7	R/W
8	A0
9	DB0
10	DB1
11	DB2
12	DB3
13	DB4
14	DB5
15	DB6
16	DB7
17	LEDA
18	LEDK

NOTES:

- 01. DISPLAY TYPE: FSTN/POSITIVE/TRANSFLECTIVE RoHS
- 02. OPERATING VOLTAGE: VOP=5.6V,VDD=5.0V
- 03. OPERATING TEMPERATURE: -20°C~+70°C
- 04. STORAGE TEMPERATURE: -30°C~+80°C
- 05. DRIVE MODE: 1/32DUTY,1/6BIAS
- 06. VIEWING DIRECTION: 6:00
- 07. DRIVE IC: SBN1661G\_M18
- 08. CONNECTOR: FPC
- 09. BACKLIGHT: WHITE
- 10. CUSTOMER'S PART ID: BLAZE\_STANDARD\_PRODUCT


**BLAZE** Blaze Display Technology Co.,Ltd.

DESIGNED BY: BDT-24

**BGB12232-11A-SERIES**

VERSION: 1.0

CHECKED BY: BDT-06



PAGE 1 OF 1

APPROVED BY: BDT-02

UNIT: mm

Website: <http://www.blazedisplay.com>

DATE: 2014-06-16