



Revised Record

1.0

New issue

2015-04-27



INTERFACE	
1	VSS
2	VDD(5V)
3	V0
4	/RD
5	/WR
6	/A0
7	DB0
8	DB1
9	DB2
10	DB3
11	DB4
12	DB5
13	DB6
14	DB7
15	/CS
16	/RES
17	VEE
18	FGND
19	LEDA
20	LEDK

Customer's Choices:

DISPLAY TYPE:	
View angle:	
Temp:	
Voltage:	
IC:	
Backlight:	
Other:	

NOTES:

- 01. DISPLAY TYPE: STN-BLUE/NEGATIVE/TRANSMISSIVE RoHS
- 02. OPERATING VOLTAGE: VOP=23V,VDD=5.0V
- 03. OPERATING TEMPERATURE: -20°C~+70°C
- 04. STORAGE TEMPERATURE: -30°C~+80°C
- 05. DRIVE MODE: 1/240DUTY,1/17BIAS
- 06. VIEWING DIRECTION: 6:00
- 07. DRIVE IC: RA8835(OR-EQV)
- 08. CONNECTOR: ZEBER
- 09. BACKLIGHT: LED(WHITE, VF: 5.0V, IF=180MA)
- 10. CUSTOMER'S PART ID: BLAZE_STANDARD_PRODUCT
- 11. ALL UNMARKED TOLERANCES: ±0.2.

BLAZE Blaze Display Technology Co.,Ltd.

DESIGNED BY: BDT-24	BGB320240-07-SERIES	VERSION: 1.0
CHECKED BY: BDT-06		PAGE 1 OF 1
APPROVED BY: BDT-02		UNIT: mm
Website: http://www.blazedisplay.com		DATE: 2015-04-27