



INTERFACE	
1	VSS
2	VDD(5V)
3	V0
4	RS
5	RW
6	E
7	DB0
8	DB1
9	DB2
10	DB3
11	DB4
12	DB5
13	DB6
14	DB7

NOTES:

- | | |
|----------------------------|--------------------------------------|
| 01. DISPLAY TYPE: | STN(Y-G)/POSITIVE/TRANSFLECTIVE RoHS |
| 02. OPERATING VOLTAGE: | VDD=5.0V VOP=4.7V |
| 03. OPERATING TEMPERATURE: | -30°C~+80°C |
| 04. STORAGE TEMPERATURE: | -35°C~+80°C |
| 05. DRIVE MODE: | 1/16DUTY,1/5BIAS |
| 06. VIEWING DIRECTION: | 6:00 |
| 07. DRIVE IC: | AIP31066 or Eqv |
| 08. CONNECTOR: | Zebea |
| 09. BACKLIGHT: | LED YELLOW-GREEN |
| 10. CUSTOMER'S PART ID: | |

BLAZE Blaze Display Technology Co.,Ltd.

DESIGNED BY: BDT-24	BCB0802-04-SERIES	VERSION: 1.0
CHECKED BY: BDT-08		PAGE 1 OF 1
APPROVED BY: BDT-05		UNIT: mm
Website: http://www.blazedisplay.com		DATE: 2014-06-06